



OPTO-EDU A59.2207-3.2M Digital Eyepiece USB CCD/CMOS Microscope Digital Eyepiece Camera

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: CNOEC, OPTO-EDU
- Certification: CE, Rohs
- Model Number: A59.2207
- Minimum Order Quantity: 1 pc
- Price: FOB \$1~1000, Depend on Order Quantity
- Packaging Details: Carton Packing, For Export Transportation
- Delivery Time: 5~20 Days
- Payment Terms: T/T, West Union, Paypal
- Supply Ability: 5000 pcs/ Month



Product Specification

- Applications: Microscope
- Certification: CE|Rohs
- Output: USB 2.0
- Product Name: Microscope Accessories
- Sensor: CMOS
- Compatible: Windows XP/Vista
- Highlight: **digital trinocular microscope, usb digital microscope**



for more products please visit us on cnoec.com

More Images



Product Description

A59.2207-3.2M Digital Eyepiece USB CCD/CMOS Microscope Digital Eyepiece Camera

- Capturing from 350K to 14M (4384x3288) pixel high quality still images
- Streaming real-time, ultra-fast, full-resolution live video on your PC screen
- High speed USB 2.0, compact design
- Fitting 4 mounting sizes: 23mm, 30mm, 30.5mm, and C-mount
- Advanced editing, processing, and measuring software
- Compatible with Windows XP/Vista/7 (32 & 64 bits)
- CE, UL, FC.. all certificate passed

A59.2207 Digital Camera, C Mount + Eyepiece Type

Our latest generation of cameras features upgraded electronics, streamlined software, and a compact design with smaller dimensions and reduced weight.

Featuring built-in C-mount compatibility and 23mm reduction lens adapter, our camera can be attached to any instrument with a C-mount or a 23mm photo port, including microscopes, telescopes, endoscopes, and etc. The camera's optics offers max 4384*3288 pixel resolution, and the included software allows you to capture real-time, high-definition videos and stills without requiring any additional equipment.

The included user-friendly software allows you to make notes, shapes, watermarks, and measurements with ease. You can analyze, present, and share images of samples and specimen by simply plugging one end into your PC's USB 2.0 port, and the other on your microscope's eye-tube or trinocular port.


In addition, the newest generation of camera comes with a preassembled 0.5X reduction lens named as Eyepiece Tube, giving your PC screen the same field of view as your microscope's eyepiece. With the reduction lens in place, your camera tube is 23mm in diameter, making it compatible with pretty much any microscope's eyetube or trinocular port! We also include 2 eyepiece adapters for FREE - 30.0mm and 30.5mm.

With its unique stand alone design, the MU series camera is equipped with CMOS color sensor, and comes with a high-speed USB 2.0 cord, advanced software (Windows XP/Vista/7 compatible), 4 mounting sizes (23mm, 30mm, 30.5mm, and C-mount), and instructions.



A59.2207 Digital Camera, C Mount + Eyepiece Type





Packing List

- One Digital Camera with Standard C-Mount
- One Eyepiece Tube, Dia.23.2mm, 0.5x Lens
- Two Ring Adaptors: Dia.30mm, Dia.30.5mm
- One 6' (1.8m) USB2.0 High-Speed Cable
- One CD with Software and User's Instructions



A59.2207 Digital Camera, C Mount + Eyepiece Type, Full Set



Pixel	350K	1.3M	2.0M	3.2M	5.2M
Senser Size	1/4.0" CMOS	1/3.0" CMOS	1/2.3" CMOS	1/2.0" CMOS	1/2.5" CMOS
Senser Size	3.58mm(H) x 2.69mm(V), Diagonal 4.48mm	4.60mm(H) x 3.70mm(V), Diagonal 5.9mm		6.55mm(H) x 4.92mm(V), Diagonal 8.19mm	5.70mm(H) x 4.28mm(V), Diagonal 7.13mm
Senser	Aptina CMOS (Color, Anti-blooming Protection)				
Output	USB2.0				
Max.Resolution	640*480	1280*1024	1600*1200	2048*1536	2592*1944
Pixel Size	5.6 x 5.6µm	3.6 x 3.6µm	2.8 x 2.8µm	3.2 x 3.2µm	2.2 x 2.2µm
Responsivity	1.9v/lux-sec(550nm)	1.0v/lux-sec(550nm)		1.0v/lux-sec(550nm)	0.53v/lux-sec(550nm)
Video Mode Format & Frame Rate	640*480/30fps 320*240/80fps	1280*1024/15fps 640*512/26fps 320*256/50fps	1600*1200/8fps 800*600/18fps	2048*1536/10fps 1024*768/22fps 680*510/43fps	2592*1944/ 5fps 1280*960/18fps 640*480/60fps
Imaging Area	3.58mm(H) x 2.69mm(V)	4.6mm(H) x 3.7mm(V)	4.73mm(H) x 3.52mm(V)	6.55mm(H) x 4.92mm(V)	5.70mm(H) x 4.28mm(V)
Dynamic Range	60dB	71dB	71dB	61dB	66.5dB
A/D Converter	10-bit Parallel, 8-bit R.G.B to PC	10-bit, 8-Bit R.G.B to PC		10-bit, 8-Bit R.G.B to PC	12-bit, 8-Bit R.G.B to PC
SN Ratio	45dB	44dB		43dB	40.5dB
Binning	1*1, 2*2	1*1, 2*2, 4*4		1*1, 2*2, 3*3	1*1, 2*2, 4*4
Exposure	0.11~192.46ms	0.140~2000ms		0.128~2000ms	0.21~2000ms
Pixel	8.0M	9.0M	10M	14M	
Senser Size	1/2.5" CMOS	1/2.3" CMOS	1/2.3" CMOS	1/2.3" CMOS	
Senser Size	5.451mm(H) x 4.088mm(V), Diagonal 6.813mm	5.825mm(H) x 4.369mm(V), Diagonal 7.281mm	6.119mm(H) x 4.589mm(V), Diagonal 7.649mm	6.138mm(H) x 4.603mm(V), Diagonal 7.672mm	
Senser	Aptina CMOS (Color, Anti-blooming Protection)				
Output	USB2.0				
Max.Resolution	3264*2448	3488*2616	3664*2748	4384*3288	
Pixel Size	1.67 x 1.67µm	1.75 x 1.75µm	1.67 x 1.67µm	1.4 x 1.4µm	
Responsivity	0.31v/lux-sec(550nm)	0.33v/lux-sec(550nm)	0.31v/lux-sec(550nm)	0.724v/lux-sec(550nm)	
Video Mode Format & Frame Rate	3264*2448/1.9fps 1600*1200/8fps 800*600/27fps	3488*2616/2fps 1744*1308/9fps 872*654/27fps	3664*2748/2fps 1832*1374/ 8fps 912*684/27fps	4384*3288/2fps	
Imaging Area	5.71mm(H) x 4.28mm(V)	6.10mm(H) x 4.58mm(V)	6.12mm(H) x 4.60mm(V)	6.13mm(H) x 4.60mm(V)	
Dynamic Range	65.2dB	62.7dB	65.2dB	65.3dB	
A/D Converter	12-bit, 8-Bit R.G.B to PC				
SN Ratio	34dB			35.5dB	
Binning	1 x 1, 2 x 2, 4 x 4				
Exposure	0.38~2000ms			0.4~2000ms	


Pixel	C800K	C1.4MA	C1.4MB	C2.0M	C3.2M
Senser Size	1/3.0" CCD	1/2.0" CCD	2/3.0" CCD	1/1.8" CCD	1/1.8" CCD
Senser Size	5.80mm(H) x 4.92mm(V), Diagonal 5.952mm	7.60mm(H) x 6.20mm(V), Diagonal 7.959mm	10.2mm(H) x 8.3mm(V), Diagonal 11mm	8.50mm(H) x 6.80mm(V), Diagonal 8.923mm	8.10mm(H) x 6.64mm(V), Diagonal 8.933mm
Senser	Aptina CCD (Color, Anti-blooming Protection)				
Output	USB2.0				
Max.Resolution	1024*768	1360*1024	1360*1024	1600*1200	2048*1536
Pixel Size	4.65 x 4.65µm	4.65 x 4.65µm	6.45 x 6.45µm	4.4 x 4.4µm	3.45 x 3.45µm
Video Mode Format & Frame Rate	1024*768 /16fps	1360*1024 /12fps	1360*1024 /15fps	1600*1200 /10fps	2048*1536 /6fps
Dynamic Range	70dB				
G Sensitivity	400mV with 1/30s Accumulation	1240mV with 1/30s Accumulation	420mV with 1/30s Accumulation	455mV with 1/30s Accumulation	
A/D Converter	12-bit Parallel, 8-bit R.G.B to PC				
SN Ratio	62dB				
Binning	1 x 1				1 x 1, 1 x 2
Exposure	Normal: 0.16~62.00ms Long Exposure: 62.98ms~4mins	Normal: 0.22~119.37ms Long Exposure: 119.37ms~4mins	Normal: 0.126~66.695ms Long Exposure: 66.695ms~4mins	Normal: 0.17~100.00ms Long Exposure: 100.00ms~4min	Normal: 0.18~77.81ms @2048 x 1536, 0.18~23.10ms @640 x 480. Long Exposure: 77.81ms~4mins
General Specification					
Scan Mode	Progressive				
Spectral Range	400-650nm (with IR-Filter) 380-1000nm (w/o IR-Filter)				
Exposure	Electronic Rolling Snap(ERS), ROI Auto & Manual,				
White balance	One Push ROI White Balance/ Manual Temp-Tint Adjustment				
Driver Interfaces	DirectShow , Twain				
Operating System	Microsoft Windows XP / Vista / 7 (32 & 64 bit) CPU: Intel Pentium 4, 2.6G or above RAM: 512 MB HDD: 10 GB USB: USB2.0 interface				
Operating Temp.	-10~60°C				
Operating Humidity	30%~80%				
Power Supply	DC 5V from PC USB port				
Package Box	140mmx140mmx80mm, 0.5Kgs				
Color Rendering Technique	Ultra FineTM Color Engine				
Capture Mode	Still Picture and Video				
Remarks	Actual frame rates on your computer depend on the hardware and operating system used				
Software Features					
Main Functions	Viewing live images; Streaming & recording live videos; Capturing & saving still images; Making measurements				
Processing	-Edits images in a similar manner to PhotoShop -Captures images, records videos and saves in JPG, TIF, GIF, PSD, WMF, and BMP formats -Add layers, watermarks, mosaics, tiles -Adjust color balance, exposure, saturation, contrast, orientation -Change resolution, histogram, granulation, diffusion -Transform images via edge detection, digital image warping				
Measurement	Measures length and angle; rectangular, elliptical and irregular areas; single, parallel and perpendicular lines				
Notation	Adds notes, measurements, text, arrows, labels, and etc. using customizable text with different sizes and colors				
Calibration	Makes measurements in microns, millimeters, centimeters, inches, feet, and etc. at all magnification settings with desired tolerances				
Driver Characteristics					
White Balance	ROI auto white balance/temp-tint manual white balance				
Black Level Calibration	Adaptive black level calibration				
Stuck or Hot Pixel	Hardware remove technique				
USB Controller Compatibility	Automatic detection of adaptation				
Interfaces Supported	DirectShow/TWAIN				
Operating System	Microsoft Windows XP / Vista / 7 (32 & 64 bit)				
Package List					
--One Digital Camera Eyepiece Type					
--One Eyepiece Tube, With Built-in 0.5x Reducing Lens					
--Two Ring Adaptors: Dia.30mm, Dia.30.5mm					
--One 6' (1.8m) USB2.0 High-Speed Cable					
--One CD with Software and User's Instructions					



Opto-Edu (Beijing) Co., Ltd.

 0086 13911110627

 sale@optoedu.com

 cnoec.com

F-1501 Wanda Plaza, No. 18 Shijingshan Road, Beijing 100043, China