



OPTO-EDU A15.2601-TT Polarizing Microscope, Transmit

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: CNOEC, OPTO-EDU
- Certification: CE, Rohs
- Model Number: A15.2601-TT
- Minimum Order Quantity: 1 pc
- Price: FOB \$1~1000, Depend on Order Quantity
- Packaging Details: Carton Packing, For Export Transportation
- Delivery Time: 5~20 Days
- Payment Terms: T/T, West Union, Paypal
- Supply Ability: 5000 pcs/ Month



Product Specification

- Highlight: **digital trinocular microscope, usb digital microscope**



More Images



for more products please visit us on cnoec.com

Product Description

Polarizing Microscope, Transmit Light, Trinocular

Transmit 5W LED Illumination+ Swing Out Condenser N.A. 0.9/0.13 Center Adjustable
 Head & Eyepiece With Joint Move Design To Keep Right Side Eyepiece's Cross Direction
 Professional Polarizing Non-Stress LWD Infinity Plan Objective (Transmitting)

Professional Polarizing Lens, Analyzer With Bertrand Lens, λ , $\lambda/4$ Slip, Quartz Wedge

Powered By Safety Low Voltage Charger, Input Wide Voltage 100V-240V, Output 5V1A, Support Power Bank Supply For Outdoor Use

Items	A15.2601 Series Polarizing Microscope	A15.2 601-T		A15.2 601-R		A15.2 601-RT		Cata. No.
		Transmit	Reflect	Transmit	Reflect	Transmit & Reflect	Transmit & Reflect	
		T B	T B	R B	R B	T B	T B	
Head	Professional Polarizing Seidentopf Binocular Head, Inclined 30°, Rotatable 360°, Interpupillary Distance 48-76mm, Eyepiece Tube Dia.30mm, Joint Move Design: Speically For Polarizing Microscope, To Keep Right Side Eyepiece's Cross In View Field Keep Vertical Direction Even When Eyepiece Tube Turned	•		•		•		A53.2625-B
	Professional Polarizing Seidentopf Trinocular Head, Inclined 30°, Rotatable 360°, Interpupillary Distance 48-76mm, Light Split Switch E100:P0/E20:P80, Eyepiece Tube Dia.30mm Joint Move Design: Speically For Polarizing Microscope, To Keep Right Side Eyepiece's Cross In View Field Keep Vertical Direction Even When Eyepiece Tube Turned		•		•		•	
Eyepiece	WF10x/22mm, Dia.30mm, High Eyepoint, Diopter Adjustable	•	•					A51.2621-1022
	WF10x/22mm, Dia.30mm, With Micrometer X-0.1mm*180 Div / Y-Single Line, Diopter Adjustable, With Position Pin For Joint Move	•	•					A51.2622-1022P
	WF10x/20mm, Dia.30mm, High Eyepoint, Diopter Adjustable			•	•	•	•	A51.2621-1020
	WF10x/20mm, Dia.30mm, With Micrometer X-0.1mm*180 Div / Y-Single Line, Diopter Adjustable, With Position Pin For Joint Move			•	•	•	•	A51.2622-1020P
Nosepiece	Quintuple, Center Adjustable	•	•	•	•	•	•	A54.2610-N02
Non-Stress Infinity Plan Objective (Transmitting)	PLAN 4x/0.10, W.D.=12.1mm	•	•			•	•	A5P.2630-4
	PLAN 10x/0.25, W.D.=4.64mm	•	•			•	•	A5P.2630-10
	PLAN 20x/0.40(S), W.D.=2.41mm	•	•			•	•	A5P.2630-20
	PLAN 40x/0.66(S), W.D.=0.65mm	•	•			•	•	A5P.2630-40
	PLAN 60x/0.8(S), W.D.=0.33mm							A5P.2630-60
	PLAN 100x/1.25(S,Oil), W.D.=0.12mm							A5P.2630-100
Non-Stress LWD Infinity Plan Objective (Reflecting)	LPL5x/0.13, W.D.=16.04mm			•	•	○	○	A5M.2633-5
	LPL10x/0.25 W.D.=18.48mm			•	•	○	○	A5M.2633-10
	LPL20x/0.40 W.D.=8.35mm			•	•	○	○	A5M.2633-20
	LPL50x/0.70(S) W.D.=1.95mm			•	•	•	•	A5M.2633-50
	LPL100x/0.90(S,Dry) W.D.=1.10mm					○	○	A5M.2633-100
Working Stage	Round Stage Diameter Φ 174mm, For Transmit Light , Rotatable 360°, Division 1', Vernier Division 6', Can Be Locked	•	•	○	○	•	•	A54.2602-S06
	Round Stage Diameter Φ 148mm, For Reflect Light , Rotatable 360°, Division 1', Vernier Division 6', Can Be Locked			•	•			A54.2602-S06a
	Attachable Mechanical Stage For Polarizing Microscope, Moving Range 40x40mm	○	○	○	○	○	○	A5P.2616
	Attachable Mechanical Stage For Polarizing Microscope, Moving Range 30x45mm, Lecia Type, Avoid Hitting Objective Lens	○	○	○	○	○	○	A5P.2616-LK
Condenser	Swing Out Condenser, N.A.0.9/0.13, With Polarizer Lens In Bottom, With Scale, Can Be Locked	•	•			•	•	A56.2614-C10

Polarizing Unit	Analyzer Media Unit, Between Head And Body, Analyzer 0~360° Adjustable, Can Be Locked, With Bertrand Lens Built-in Focus Adjustable,	●	●	●	●	●	●	A5P.2621-BK
	Compensator Slide, With λ Slip (First Class Red)	●	●	●	●	●	●	A5P.2614-16a
	Compensator Slide, With $\lambda/4$ Slip	●	●	●	●	●	●	A5P.2614-15a
	Quartz Wedge Slide (I-IV Class)	●	●	●	●	●	●	A5P.2615-17
	Quartz Wedge Slide (0-IV Class) Long Type	○	○	○	○	○	○	A5P.2615-17a
	Polarizer Lens, Built-in Bottom Part Of Condenser	●	●	●	●	●	●	A5P.2610-BK
Focusing	Coaxial Coarse & Fine Focusing, Coarse Focusing Travel Range: 22mm, Fine Focusing Div. 0.002mm	●	●	●	●	●	●	
Illumination	Transmit Light 5W LED Koehler Illumination, Powered By Safety Low Voltage Charger, Input Wide Voltage 100V-240V, Output 5V1A, Support Power Bank Supply For Outdoor Use	●	●			●	●	A56.2612-5W
	Transmit Light 6V30W Halogen Koehler Illumination, Wide Voltage 100V~240V	○	○			○	○	A56.2613-30W
	Reflect Light 5W LED Koehler Illumination, Powered By Safety Low Voltage Charger, Input Wide Voltage 100V-240V, Output 5V1A, Support Power Bank Supply For Outdoor Use				●	●	●	A56.2612-5W
	Reflect Light 12V50W Halogen Koehler Illumination, Wide Voltage 100V~240V			○	○	○	○	A56.2613-50W
Field Diaphragm	For Kohler Illumination	●	●	●	●	●	●	A56.2615-BK
Power	ECO, Auto Power Off System. Power Off Automatically Upon User Leaving 10 Minutes, Power On Automatically Upon User Approaching Detected, This Function Can Be Shut Down Manually	○	○			○	○	A56.2660
Filter	Dia.45mm, Blue	○	○	○	○	○	○	A56.2616-45B
	Dia.45mm, Green	○	○	○	○	○	○	A56.2616-45G
	Dia.45mm, Yellow	○	○	○	○	○	○	A56.2616-45A
Adapter	C-Mount 0.5x, Focus Adjustable		○		○		○	A55.2601-05
	C-Mount 0.75x, Focus Adjustable		○		○		○	A55.2601-75
	C-Mount 1.0x, Focus Adjustable		○		○		○	A55.2601-10
	Digital Eyepiece Camera Adapter, Dia. 23.2mm/25mm		○		○		○	A55.2610
Package & Weight	Carton Size 520×470×285mm, 1 Unit/Ctn, Gross Weight: 12.5 kgs, Net Weight: 10.0 kgs							A15.2601-TB,TT
	Carton Size 520×470×430mm, 1 Unit/Ctn, Gross Weight: 16.0 kgs, Net Weight: 12.5 kgs							A15.2601-RB,RT
	Carton Size 520×470×430mm, 1 Unit/Ctn, Gross Weight: 15.0 kgs, Net Weight: 11.5 kgs							A15.2601-RTB,RTT
Note: "●" In Table Is Standard outfits, "○" Is Optional Accessories								



OPTO-EDU (BEIJING) CO., LTD.

F-1501 Wanda Plaza, No.18 Shijingshan Road, Beijing 100043, China
Tel:+8610 88696020 Fax:+8610 88696085

A15.2601

Polarizing Microscope, Transmit & Reflect



A15.2601 Series Polarizing Microscope



Product Details



Super Wide Field Eyepiece
SWF 10x/22mm
Eyepiece Dia. 30mm Diopter Adjustable



The Eyepiece Tube Has Fix Screw
To Prevent Eyepiece Falling Damage During Move
Dia. 30mm

Retical Eyepiece WF10x/20mm, Dia.30mm
 With Micrometer X-0.1mm*180 Div / Y-Single Line, Diopter Adjustable
 Joint Move Design: Specially For Polarizing Microscope, To Keep Right Side Eyepiece's Cross In View Field Keep Vertical Direction Even When Eyepiece Tube Turned.



Trinocular Head Light Split Optional Between Switch E100:P0/E0:P100 & Fixed E80:P20
 In Fixed Light Split, Eyepiece 80% : Photo 20% User Can View Image At Same Time In Both Path
 In Switch Light Split, Eyepiece 100%:Photo 0% / Eyepiece 0%:Photo 100%, Camera Can Have 100% Light For Photo Capture.

Product Accessories



A5P.2630 Non-Stress Infinity Plan Objective (Transmitting)



A15.2601-T Polarizing Microscope Transmit Polarizing Unit



A55.2601-05
C-Mount 0.5x
Focus Adjustable



A55.2601-75
C-Mount 0.75x
Focus Adjustable



A55.2601-10
C-Mount 1.0x
Focus Adjustable



A55.2610
Digital Eyepiece
Camera Adapter
Dia. 23.2mm/25mm



A5P.2616-LK Attachable Mechanical Stage, Lecia Type




A5P.2616 Attachable Polarizing Mechanical Stage, Moving Range 40x40mm



A5P.2615-17a Quartz Wedge Slide (0-IV Class) Long Type



A56.2615-BK Field Diaphragm For Kohler Illumination



A56.2616 Filter: Dia.45mm Blue, Green, Yellow



A54.2610-N02 Quintuple, Center Adjustable



Opto-Edu (Beijing) Co., Ltd.

☎ 0086 13911110627

✉ sale@optoedu.com

🌐 cnoec.com

F-1501 Wanda Plaza, No. 18 Shijingshan Road, Beijing 100043, China